

**DATA
SHEET
BT-2515****2500 bar Hand Pump**

This hand pump can be used with all BOLTIGHT 2500 bar tooling and equipment. The pump has both high and low pressure pistons and is supplied complete with, a 110 mm diameter pressure gauge, pressure release valve, internal pressure safety relief valve (set at 2500 bar), a 2.4 litre oil reservoir and a self sealing quick connect coupling (Type C) fitted with a red plastic dust cap.

Hand pumps should only be used with one or two tensioning tools. When simultaneous operation of several tools is being considered BOLTIGHT recommends the use of an air driven pump.

Part No BT-2515

**Steel Pump Block and Handle****Strong 2.4 litre Aluminium
Extrusion Oil Reservoir****Specification:**

Part No	BT-2515
Dimensions	620 mm long x 130 mm wide x 170 mm high
Weight	11 kgs
Oil Reservoir	2.4 litre ISO 10 hydraulic oil
Finish	Aluminium Silver and Black
Pressure Gauge	0 - 3000 bar 0 - 45,000 psi
Maximum Pressure	2500 bar
Internal Pressure Relief Valve set at	2500 bar
Oil Delivery Low Pressure Piston	20 cc per stroke
Oil Delivery High Pressure Piston	0.8 cc per stroke
Handle Effort @ 2500 bar	420 Newtons